

**BLACK POLYPROPYLENE MASTERBATCH FOR
MOULDING AND EXTRUSION APPLICATIONS**



PLASBLAK® PP6190



PLASBLAK® PP6190 is designed for high quality moulding and extrusion applications. Typical application areas include injection moulding, sheet, tape and PP staple fibre. PLASBLAK® PP6190 exhibits good dilutability together with optimum carbon black dispersion characteristics and gives excellent protection against UV light degradation.

This product is suitable for use in a wide range of plastics that come into contact with food . For more details regarding the food contact compliance in various European countries, please refer to the relevant Food Contact Statement that you can obtain through your usual Cabot representative.

METHOD OF ADDITION

PLASBLAK® PP6190 is designed for ease of dilution and homogeneous mixing and is therefore suitable for direct addition using automatic dosing units or by pre-blending.

ADDITION RATE

The amount of masterbatch added depends on the performance requirements of the final application. Typical addition rates vary from 2% to 7% masterbatch, for maximum UV protection 7% is recommended.



Cabot Corporation

www.cabot-corp.com/plastics

PLASBLAK® PP6190

BLACK POLYPROPYLENE
MASTERBATCH FOR MOULDING AND
EXTRUSION APPLICATIONS



PHYSICAL PROPERTIES

PROPERTY	VALUE	TEST METHOD (*)
Carrier	polypropylene	
Pigment	35 % carbon black	
Additive	antioxidant	
Compatibility	PP	
Density @ 23°C	1094 kg/m ³	CTM E023
MFI (5 kg/230°C)	9 g/10 min	CTM E005 (ISO 1133)

(*) Tests are performed according to Cabot Test Methods (CTM) based on international Standards

Quoted test results should not be used for specification purposes but are typical test values intended for guidance only.

PACKAGING

PLASBLAK® PP6190 is supplied in regular pellet form packed in 25 kg bags. It should be stored in a dry place. Recommended storage life: up to 1 year provided it is stored as directed.

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.

HEAD OFFICE
Cabot SCCC
Interleuvenlaan 15 I
B - 3001 Leuven - Belgium
Tel : +32 16 39 24 00
Fax : +32 16 39 24 44
SALES OFFICES
Cabot Plastics Hong Kong Ltd
18 Dai Kwai Street
Tai Po Industrial Estate / NT
Hong Kong SAR - PRC
Tel: +852 2666 2666
Fax: +852 2666 0807

Cabot Plastics Belgium S.A.
Rue Prevochamps 78
B - 4860 Pepinster - Belgium
Tel: +32 87 39 27 11
Fax: +32 87 46 98 69

Cabot Latin America Division
Rua do Paraíso, 148 – 5th floor
Paraíso CEP 04103-000 São Paulo SP -
Brazil
Tel: +55 11 21 44 64 00
Fax: +55 11 32 53 00 51
Tel.: (0800) 195 959 (Customer Service)

Cabot Plastics Deutschland
Tel: (0800) 182 40 86
Fax: (0800) 182 40 87
c/o Cabot Plastics Belgium S.A.
(see address on the left)

Cabot Italiana S.p.A
Zona Industriale, 4
I - 38055 Grigno (TN) - Italia
Tel: +39 0461 775 211
Fax: +39 0461 765 146

中国
卡博特(中国)投资有限公司
中国上海吴淞双柏路558号
邮编: 201108
电话: +86 21 6434-7766
传真: +86 21 6434-5532

PLASBLAK®, PLASWITE®, PLASGREY®, PLASADD®, CABELECC® and CABOT® are registered trademarks of Cabot Corporation
© Cabot Corporation, MA, U.S.A. All rights reserved. 2010